



## Large Can Aluminum Electrolytic Capacitors

Series	Feature	Terminal Type	Rate Voltage Range(V)	Nominal Capacitance Range(μF)	Capacitance Tolerance	Operating Temperature Range( °C)	Case Dimension Range inch(mm)	
							Diameter	Length
CD293	85°C Miniaturize	Snap-in	10~450	68~22000	± 20%	- 40~+85	0.79(20)~1.38(35)	0.87(22)~ 1.97(50)
CD293H	105°C Miniaturize	Snap-in	10~450	68~47000	± 20%	- 40~+105	0.79(20)~1.38(35)	0.87(22)~ 1.97(50)
CD135	85°C Miniaturize	Screw	10~250	680~820000	± 20%	- 40~+85	1.38(35)~ 3.50(89)	2.28(58)~6.30(160)
CD135	85°C Miniaturize	Screw	315~450	270~39000	± 20%	- 40~+85	1.38(35)~ 3.50(89)	2.28(58)~6.30(160)
CD136	105°C Long Life	Screw	10~100	1800~680000	± 20%	- 40~+105	1.38(35)~ 3.50(89)	1.97(50)~ 5.51(140)
CD136	105°C Long Life	Screw	160~400	180~27000	± 20%	- 25~+105	1.38(35)~ 3.50(89)	1.97(50)~ 5.51(140)
CD13A	Power Supplies 85°C For Inverter	Screw	350~450	1000~18000	± 20%	- 40~+85	2.01(51)~ 3.50(89)	3.15(80)~ 9.45(240)
CD13AH	Power Supplies 105°C For Inverter	Screw	350~450	1000~15000	± 20%	- 40~+105	2.01(51)~ 3.50(89)	3.15(80)~ 9.45(240)
CD13	85°C Miniaturize	Lug	16~100	470~68000	-10%+50%	- 40~+85	0.87(22)~ 1.57(40)	1.18(30)~ 3.94(100)
CD13	85°C Miniaturize	Lug	160~450	33~2200	-10%+50%	- 25~+85	0.87(22)~ 1.57(40)	1.18(30)~ 3.94(100)
CDWM	85°C Miniaturize	Screw	25~450	220~55000	-20%+50%	- 25~+55	1.65(42)~ 3.15(80)	3.94(100)~ 4.72(120)
CD60	85°C Miniaturize	Lug	110~330AC	25~500	0%+20%	- 20~+70	0.98(25)~ 2.01(51)	1.57(40)~ 3.94(100)
CD17	85°C Miniaturize	Lug	330,360	150~1500	-10%+20%	- 20~+55	0.55(14)~ 1.38(35)	1.00(25.5)~ 2.87(73)
CDIN	85°C Miniaturize	Lug	400,450	1000~2400	± 20%	- 25~+85	1.57(40)~ 2.50(63.5)	3.15(80)~ 4.72(120)
CDPC	85°C Miniaturize	Lug	250	90~440	± 10%	- 25~+85	1.38(35)~ 1.57(40)	3.15(80)~ 3.94(100)
CDPC	85°C Miniaturize	Snap-in	400	45~220	± 10%	- 25~+85	1.18(30)~ 1.38(35)	1.57(40)~ 2.09(53)